## **DECLARATION OF PERFORMANCE**

SalzM-CRP-2014/09/25-GB



**PRODUCT** 

**Product type** Slow heat release appliance

Type designation Salzburg M

**Product identification** See product instruction manual

Intended area of use Heating of rooms in residential buildings

**Fuel** Wood

**MANUFACTURER** 

Name Nordpeis AS

Adress Gjellebekkstubben 11

3420 Lierskogen, Norway

**CHECKS** 

According to AVCPSystem 3StandardEN 15250:2007

**Test institute** Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625

has checked declared performance and issued test report no. RRF- 50 11 2758 / RRF- 50 14 3624

## **DECLARED PERFORMANCE**

				Harmonized
Essential Characteristic		Performance		
				specification
Reaction to fire	A1 WT			
Minimum distances to combustible material	50	mm rear		
	100	100 mm side		
	other safe	other safety distances		
	according	g product ma		
Risk of falling embers	Approved	Approved		
Emission from combustion:				
Carbon monoxide at 13% O <sub>2</sub>	CO =	0,095	% Vol	
Oxygen nitride NOx at 13% O <sub>2</sub>	NOx =	142	$mg/m^3$	
Organic Gaseous Carbon at 13% O <sub>2</sub>	OGC =	81	$mg/m^3$	
Particulate Matter at 13 O <sub>2</sub>	PM =	32	mg/m³	EN 15250:2007
Surface temperatures	Approved	Approved		
Cleanability	Approved	Approved		
Mechanical durablity	Approved	Approved		
Releases of Hazardous Substances	Approved	t		_
Total thermal output		39,4	kWh	_
Nominal output after elapsed time at 25% of max. mean temperature	P =	2,40	kW	_
Flue gas temperature at nominal output	t <sub>a</sub> =	157	°C	_
Energy efficiency	η=	84,0	%	

The udersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS